



เครื่องปรับอากาศ “แคเรียร์”



42JBX/JB Series

Floor/Ceiling Type

13,000-60,000 BTUH



42JBX/JB Series



42JB Series

42JBX Series

Designed for Optimised Individual Comfort

The new **42JBX/JB Series**, floor/ceiling type, offer concentrated high technology in an aesthetically pleasing design. The units are compact, extremely slim and blend in harmoniously with any office or residential environment. Available from 13,000-60,000 BTU with the same modern aesthetic, they create the art of comfort in all residential and small commercial applications.



The **infrared remote control** of the 42JBX/JB Series unit is very simple to use and controls all air conditioning functions. Its main characteristics are

- 24 hours programming
- Large Liquid Crystal Display
- Selectable fan speed: high, medium, low or automatic.

Digital wire remote control can use with wireless remote control.

Wireless Remote Control



Wire Remote Control



Digital Wire Remote Control (Optional for 42JB Series only)



38RB/RC 010-024

38RB 032

38RB 036-060

Condensing unit is turbo cool system and have inner groove tube. Tube increased performance ventilate in Condensing unit and save electricity more than 10%.

Specifications

Description		Type	Floor/Ceiling												
Model	Outdoor	38RB/RC													
		012	016	018	020	024	032	036B	040B	032T	036	040	048	060	
Model	Indoor	42JBX/JB													
		004	006	006	006	008	010	012	014	010	012	014	016	020	
Cooling Capacity*	BTU/Hr	13,000	16,000	19,000	20,000	25,000	33,000	36,000	40,000	33,000	36,000	40,000	48,000	60,000	
Power Supply	V/Ph/Hz	220/1/50									380/3/50				
Current (RLA)**	Rotary	AMP	6.40	8.20	9.60	10.00	11.10	16.10	-	-	-	-	-	-	
	Scroll	AMP	-	-	9.49	9.89	10.87	15.74	18.20	20.40	6.90	7.80	8.40	10.10	11.12
Power Input	Rotary	Watt	1,218	1,535	1,874	1,980	2,375	3,280	-	-	-	-	-	-	
	Scroll	Watt	-	-	1,795	1,960	2,350	3,170	3,546	3,970	3,085	3,485	3,915	4,475	5,740
Indoor Air Circulation	CFM	400	600	600	600	800	1,000	1,200	1,400	1,000	1,200	1,400	1,600	2,000	
Dimension (Outdoor/Indoor)	Height	mm.	525/620	525/620	570/620	570/620	570/620	670/620	1080/620	1080/620	670/620	1080/620	1080/620	1080/620	1080/620
	Width	mm.	800/978	800/1278	840/1278	840/1278	840/1278	840/1278	840/1770	840/1770	840/1278	840/1770	840/1770	840/1770	840/1770
	Depth	mm.	250/200	250/200	300/200	300/200	300/245	330/245	330/245	330/245	330/245	330/245	330/245	330/245	330/245
Net Weight (Outdoor/Indoor)	kg.	39/32	42/37	46/37	51/37	58/54	69/54	86/69	97/72	69/54	86/69	97/72	104/76	108/79	
Refrigerant			R-22												
Connections	Liquid	in.	1/4	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8
	Suction	in.	1/2	5/8	5/8	5/8	5/8	5/8	3/4	7/8	5/8	3/4	7/8	7/8	7/8
Type of Compressor			Rotary/Scroll												

* COOLING CAPACITY BASED ON ENTERING AIR TEMP. 80°F. DB/67°F.WB, AMBIENT TEMP. 95°F.DB

** RLA: RATED LOAD AMPERE

Carrier reserves the right to make changes in specifications without prior notice. บริษัทฯ ขอสงวนสิทธิ์ที่จะเปลี่ยนแปลงรายละเอียดข้างต้น โดยไม่ต้องแจ้งให้ทราบล่วงหน้า

บริษัท แคนเรีย (ประเทศไทย) จำกัด

ชั้น 14-15 อาคารเนชั่น ทาวเวอร์
46/63-74 ถ.บางนา-ตราด กม. 4.5
บางนา กรุงเทพฯ 10260
โทร. 0-2751-4777 แฟกซ์: 0-2751-4778

Carrier (Thailand) Ltd.

14-15th Fl., Nation Tower,
46/63-74 Bangna-Trad Road Km. 4.5, Bangna,
Bangkok 10260 Thailand
Tel.: 0-2751-4777 Fax: 0-2751-4778



YOUR CARRIER MAN :